

## Computational modelling and characterization of non-Newtonian visco-plastic cementitious building materials

Mareike Thiedeitz<sup>1</sup>, Jithender J. Timothy<sup>2</sup> and Thomas Kränkel<sup>3</sup>

Technical University Munich, Centre for Building materials,

<sup>1</sup> [mareike.thiedeitz@tum.de](mailto:mareike.thiedeitz@tum.de), <sup>2</sup> [jithender.timothy@tum.de](mailto:jithender.timothy@tum.de), <sup>3</sup> [thomas.kraenkel@tum.de](mailto:thomas.kraenkel@tum.de)

**Key Words:** *non-Newtonian flow, cement paste, computational fluid dynamics, visco-plastic modelling, concrete rheology*

Cementitious building materials like Ultra High Performance concrete (UHPC), Self-Compacting Concrete (SCC) or concrete with low clinker content (Green Concrete) possess a complex rheological behaviour due to high packing densities and the use of various additives and chemical admixtures. Existing rheological models such as the visco-plastic BINGHAM or HERSCHEL-BULKLEY model do not fit the actual flow behaviour of strongly non-Newtonian cementitious materials: Depending on the paste mix design of a concrete, a huge range of non-Newtonian flow characteristics from shear-thinning to shear-thickening and visco-elastic material behaviour can appear. Computational modelling of transient concrete flow therefore requires accurate knowledge of the rheological properties, followed by a meaningful choice of both the rheological model for computational fluid dynamics simulation (CFD) and the associated boundary conditions. The authors present a test program of four cementitious pastes with low ( $\phi = 0.45$ ) and high ( $\phi = 0.55$ ) solid volume fraction  $\phi$  each with low and high flowability. A rheological analysis will serve as input for the numerical modelling of concrete flow. CFD analysis using OpenFoam is conducted for a mini-L-Box test using the yield stress function incorporating BINGHAM- and HERSCHEL-BULKLEY equations and viscosity-related Cross- and adapted shear-thickening equations. Experimental mini-L-Box tests are compared with CFD results. With increasing non-Newtonian behaviour, numerical instabilities and deviation from actual flow behaviour is shown. This is especially valid at the transition from visco-plastic to visco-elasto-plastic material behaviour. The results provide new insight into computational modelling of complex cementitious building materials and serves as basis for further advanced CFD based modelling and characterization of time-dependent non-Newtonian concrete flow.