Water-induced ageing modification factor for PTFE-coated glass fibre fabric

X International Conference on Textile Composites and Inflatable Structures – STRUCTURAL MEMBRANES 2021

H. Asadi ^{*}, J. Uhlemann ^{*}, N. Stranghoener ^{*}, and M. Ulbricht [†]

^{*} University of Duisburg-Essen, Institute for Metal and Lightweight Structures, Universitaetsstr. 15, 45141 Essen, Germany

Email: hastia.asadi@uni-due.de, joerg.uhlemann@uni-due.de, natalie.stranghoener@uni-due.de

Web page: www.uni-due.de/iml

[†] University of Duisburg-Essen, Lehrstuhl für Technische Chemie II, Universitaetsstr. 7, 45117 Essen, Germany

Email: mathias.ulbricht@uni-essen.de - Web page: <https://www.uni-due.de/tech2chem>

ABSTRACT

The negative impact of water must be considered during the design of architectural coated woven fabrics which are sensitive to water attacks. It is known that the uniaxial tensile strength of glass-PTFE materials does degrade with water attack. This contribution quantifies the possible tensile strength reduction of different types of glass-PTFE materials under various water exposure conditions. This includes not only water exposure of unsealed cutting edges, as they, e. g., exist in weld seams, but also water exposure of the glass fibres through the PTFE coating. Experimental results show that both water exposure methods lead to similar degradation effects. From the acquired values of degradation, strength modification factors have been derived using the principles of the new European Technical Specification prCEN/TS 19102 “Design of tensioned membrane structures”.

KEYWORD: Tension fabric structure, glass-PTFE materials, water impacts, uniaxial tensile strength, and weathering-induced ageing modification factors