Metric-based adaptive mesh refinement and flux error in CFD problems

IX International Conference on Adaptive Modeling and Simulation – ADMOS 2021

L. Prouvost*, A. Belme* and D. Fuster*

* Sorbonne Université, CNRS, IJLRDA UMR 719
4 Place Jussieu, T. 55-65
75252 Paris, France
e-mail: lucas.prouvost@sorbonne-universite.fr

ABSTRACT

The present conference paper discusses a new adaptive mesh refinement (AMR) method implemented in our in-house open-source solver Basilisk [2]. The solver uses a cell-centered volume of fluid (VOF) approach [5] for the numerical resolution on isotropic octree/quadtrees meshes. The current AMR method is meant to improve the accuracy of resolution namely when dealing with multi-scale problems with or w/o singularities or multi-phase flows [4].

The novel AMR approach uses a metric-based error estimation of the linear interpolation error for some field [1] and a flux error involving the model equation without the use of a dual problem. This metric-based approach has been compared with the wavelet-based AMR implemented in Basilisk [3].

In order to assess the efficiency of our new AMR approach, we test the performance of the method for the reaction-diffusion equation. In particular, we use a multi-scale problem with known solution composed of a high amplitude and high frequency oscillation and several low amplitude and low frequency oscillations (Figure 1). This problem, while simple, is shown to be a challenging test case to evaluate the performance of AMR methods.

Figure 1 : (Left) : Solution field. (Right) AMR mesh obtained for the multi-scale function

The grid obtained is able to capture the different scales present in the problem. Comparing the global error convergence in L^1 norm versus the square root of the number of cells (Figure 2), we clearly see that the native wavelet-based AMR method is not able to reduce the error with respect to a cartesian grid. Remarkably, the new proposed method significantly reduces the error introduced in the solution for a given number of grid cells getting close to the optimal performance expected for a quadtree grid.

Figure 2 : Comparison of error convergence for two AMR methods for a specific reaction-diffusion equation.

Register for free at <https://www.scipedia.com> to download the version without the watermark

The adaptation of the current approach to standard incompressible Euler and Navier-Stokes flow solver is currently under study.

REFERENCES

1. F. Alauzet and A. Loseille, « A decade of progress on anisotropic mesh adaptation for computational fluid dynamics », *Computer-Aided Design*, 72 (2016) 13-39
2. S. Popinet, « A quadtree-adaptative multigrid solver for the Serre-Green-Naghdi equations », *Journal of Computational Physics*, Elsevier, 2015, 302, pp.336-358.
3. J. Antoon van Hooft, Stéphane Popinet, Chiel C. van Heerwaarden, Steven J.A. van der Linden, Stephan R. de Roode, and Bas J.H. van de Wiel. « Towards adaptive grids for atmospheric boundary-layer simulations ». *Boundary-Layer Meteorology*, 167(3):421–443, 2018.
4. J. Bourguille, L. Bergamasco, G. Tahan, D. Fuster, M. Arrigoni, « Shock Propagation Effects in Multilayer Assembly Including a Liquid Phase », *Key Engineering Materials*, Vol. 755, pp. 181-189, 2017
5. D. Fuster and S. Popinet, « An all-Mach method for the simulation of bubble dynamics problems in the presence of surface tension », *J. of Comp. Physics*, Vol 374, pp. 752-768, 2018