Geometrically exact integral-based nonlocal model of ductile damage: basic properties and numerical treatment

Alexey V. Shutov^{*,†,‡}, Vladislav S. Klyuchancev^{†,‡}

[†] Lavrentyev Institute of Hydrodynamics
Pr. Lavrentyeva 15, 630090 Novosibirsk, Russia

[‡] Novosibirsk State University
Ul. Pirogova 2, 630090 Novosibirsk, Russia

Email: alexey.v.shutov@gmail.com - Web page: <http://sites.google.com/site/materialmodeling>

ABSTRACT

We develop the integral approach [1] for the analysis of nonlocal ductile damage in metals. The starting point is the previously proposed phenomenological model of finite strain plasticity [2]. The original damage model is delocalized by the averaging operator [1], applied to damage-related quantities like porosity and continuity. Depending on the implemented delocalization procedure, at least one internal length parameter is introduced into the formulation. As a result, the damage localization is controlled by the presence of length-like parameters, thus regularizing the boundary value problem. Owing to the regularization, numerically robust and physically sound simulations of crack initiation and propagation are possible. Unphysical localization of strain and damage into a zero thickness layer is effectively prevented. From the theoretical standpoint, the basic properties of the new material model are analysed. Model's thermodynamic consistency, objectivity, and w-invariance [3] are established. Efficient numerical algorithms are proposed. To test the robustness of the integral-based approach, low-order meshless smoothed particle simulations are carried out. As a demonstration problem, we simulate crack initiation and propagation in a compact tension specimen. The resulting force-displacement curves, apparent fracture toughness, energy dissipation, and patterns of damage distribution provide insight into the mechanical phenomena, captured by the framework. The impact of the modelling assumptions on the predicted structural strength is clarified: Isotropic and anisotropic averaging is discussed; the delocalization is applied on various configurations; continuity is introduced as a dual damage variable to minimize the unrealistic diffusion of damage.

The study was supported by the Russian Science Foundation within the project 19-19-00126.

REFERENCES

- [1] Z.P. Bažant and M. Jirásek, “Nonlocal Integral Formulations of Plasticity and Damage: Survey of Progress”, *Journal of Engineering Mechanics*, **128**, 1119-1149 (2002).
- [2] A.V. Shutov, C.B. Silbermann and J. Ihlemann, “Ductile damage model for metal forming simulations including refined description of void nucleation”, *International Journal of Plasticity*, **71**, 195-217 (2015).
- [3] A.V. Shutov and J. Ihlemann, “Analysis of some basic approaches to finite strain elastoplasticity in view of reference change”, *International Journal of Plasticity*, **63**, 183-197 (2014).