CONSIDERATIONS ON RELATIONSHIP BETWEEN EACH SENSITIVITY TERM AND RESULTS OF TOPOLOGY OPTIMIZATION IN UNSTEADY OSCILLATION PROBLEM FOR 3D CANTILEVER BEAM

MASAYUKI KISHIDA¹ AND TAKAHIKO KURAHASHI¹

¹ Nagaoka University of Technology
1603-1, Kamitomioka, Nagaoka, Niigata 940-2188, Japan
E-mail s173029@stn.nagaokaut.ac.jp

Key words: Topology optimization, Density method, Self-adjoint, Sensitivity terms

Abstract. In this study, we carried out the topology optimization based on the density method in the unsteady oscillation problems. This paper considers two items, the proposal of new performance function and the relationship between each sensitivity term and results of topology optimization. In other studies, the adjoint analysis must be performed for the propose of minimizing strain energy. Optimization problems are classified into the problem of maximizing work in the negative and the problem of minimizing work in the positive, and self-adjoint relationships are derived. When using this method for cantilever beam model, there is a problem that numerous high-density elements is distributed at the load point, i.e., the tip. By classifying the sensitivity, it is found that the mass term has a great influence on the problem. In our study, some results are shown by changing the penalization parameter in the SIMP method that determines the mass coefficient, damping coefficient and elastic coefficient.

1 INTRODUCTION

Topology optimization is especially useful in improving the performance and reducing the weight of products [1]. In other researches, the performance function for the unsteady oscillation problems is set to the natural frequency or the square of strain energy[2]. Thus, it is to find the optimal structure without adjoint analysis in topology optimization for unsteady oscillation problem. In this paper, a new performance function is proposed, and self-adjoint relationships are derived by classifying optimization problem into maximization and minimization problem. More details will be given in the next chapter. When the above method is applied to the optimization problem, a lot of density elements are distributed at the load point in the cantilever beam model. The reason is that when the sensitivity is classified into three terms, i.e., terms including mass matrix, terms including damping matrix and terms including stiffness matrix, the sensitivity of the terms including stiffness matrix is high at the load points (See Figure 1). From Figure 1, in order to clarify the relationship between each sensitivity term and the results of topology optimization, the penalization parameters of the Solid Isotropic Material with Penalization (SIMP) method, which is one of the density method, is changed and investigated. Chapters 2 and 3 describe the formulation and the flowchart for topology optimization in the unsteady oscillation problems, and Chapter 4 describes an example of numerical experiments.

(a) Only terms including mass matrix.

(b) Only terms including damping matrix.

(c) Only terms including stiffness matrix.

Figure 1: Sensitivity distributions of each term at the first iteration.

2 FORMULATION FOR TOPOLOGY OPTIMIZATION

This chapter describes the formulation for topology optimization in the unsteady oscillation problems. The aim of this optimization analysis is the minimizing of the strain energy that satisfies the target volume. The strain energy is usually zero when summed over the entire time. Thus, the strain energy can be classified into the work in the positive and the work in the negative. The performance function is set in which the work in the positive is a minimization problem and the work in the negative is a maximization problem. Constraint conditions apply the governing equation, the volume constraint and the density constraint. The performance function and constrain conditions are written as

$$\min_{e \in \Omega} J = \int_0^{t_f} \int_{\Omega} J_e d\Omega dt \quad (1)$$

Register for free at <https://www.scipedia.com> to download the version without the watermark

$$\text{subject to } \int_0^{t_f} \int_{\Omega} [M(\rho_e)] \{\ddot{u}\} + [C(\rho_e)] \{\dot{u}\} + [K(\rho_e)] \{u\} d\Omega dt = \int_0^{t_f} \int_{\Omega} \{f\} d\Omega dt \quad (3)$$

$$V = \int_{\Omega} \frac{\rho_e v_e}{V_{total}} d\Omega - \bar{\rho}_0 \leq 0 \quad (4)$$

$$0 \leq \rho_e \leq 1 \quad (5)$$

where $[M]$, $[C]$, $[K]$, $\{\ddot{u}\}$, $\{\dot{u}\}$ and $\{u\}$ are, respectively, the mass matrix, damping matrix, stiffness matrix, acceleration vector, velocity vector and displacement vector. And, e , t_f , ρ , v , V_{total} and $\bar{\rho}_0$ are, respectively, the element number, final time, non-dimensional density, an element volume, sum of element volumes in the design domain Ω and average initial density in the design domain Ω . $[M]$, $[C]$ and $[K]$ are assumed to be a function of density ρ_e in the element e . Here, the final time t_f is set as enough time for the displacement to be infinitely close to zero. The Lagrange multiplier method is used to determine the density gradient, as shown in Equation (6). In order to obtain the displacement gradient, it is divided into the case of the minimization problem and the case of minimization problem, that is,

the case of work in the positive and the case of work in the negative. For the work in the positive, the displacement gradient can be calculated as in Equation (7), and for the work in the negative, the displacement gradient can be calculated as Equation (8). From Equations (7) and (8), the self-adjoints are $\{\lambda\} = -\{u\}$ and $\{\lambda\} = \{u\}$, respectively. It is not necessary to perform the adjoint analysis by using the self-adjoint relationships, as shown in Equation (9).

$$\begin{aligned} L &= \int_0^{t_f} \int_{\Omega} J_e + \frac{1}{2} \{\lambda\}^T ([M(\rho_e)] \{\ddot{u}\} + [C(\rho_e)] \{\dot{u}\} + [K(\rho_e)] \{u\} - \{f\}) d\Omega dt \\ &= \int_0^{t_f} \int_{\Omega} L_e d\Omega dt \end{aligned} \quad (6)$$

$$\frac{\partial L_{e_p}}{\partial u} = \sum_+ \frac{1}{2} \int \frac{\partial \{u\}^T}{\partial u} \left(\{f\} + [M(\rho_e)] \{\ddot{\lambda}\} - [C(\rho_e)] \{\dot{\lambda}\} + [K(\rho_e)] \{\lambda\} \right) dt = 0 \quad (7)$$

$$\frac{\partial L_{e_n}}{\partial u} = \sum_- \frac{1}{2} \int \frac{\partial \{u\}^T}{\partial u} \left(-\{f\} + [M(\rho_e)] \{\ddot{\lambda}\} - [C(\rho_e)] \{\dot{\lambda}\} + [K(\rho_e)] \{\lambda\} \right) dt = 0 \quad (8)$$

$$\begin{aligned} \frac{\partial L_e}{\partial \rho_e} &= \frac{1}{2} \int_0^{t_f} \{\lambda\}^T \left(\frac{\partial [M(\rho_e)]}{\partial \rho_e} \{\ddot{u}\} + \frac{\partial [C(\rho_e)]}{\partial \rho_e} \{\dot{u}\} + \frac{\partial [K(\rho_e)]}{\partial \rho_e} \{u\} \right) dt \\ &= \sum_+ \frac{1}{2} \int -\{u\}^T \left(\frac{\partial [M(\rho_e)]}{\partial \rho_e} \{\ddot{u}\} + \frac{\partial [C(\rho_e)]}{\partial \rho_e} \{\dot{u}\} + \frac{\partial [K(\rho_e)]}{\partial \rho_e} \{u\} \right) dt \\ &\quad + \sum_- \frac{1}{2} \int \{u\}^T \left(\frac{\partial [M(\rho_e)]}{\partial \rho_e} \{\ddot{u}\} + \frac{\partial [C(\rho_e)]}{\partial \rho_e} \{\dot{u}\} + \frac{\partial [K(\rho_e)]}{\partial \rho_e} \{u\} \right) dt \end{aligned} \quad (9)$$

Here, the subscripts + and - represent the case of work in the positive and the case of work in the negative. Optimality Criteria (OC) method is used for density update[3]. When the density is updated, the move limit is set to satisfy the density constraint. The density update equation and move limit of density are written as

Register for free at <https://www.scipedia.com> to download the version without the watermark

$$\rho_e^{(k+1)} = \rho_e^{(k)} \left(\frac{\frac{\partial M}{\partial \rho_e} (k)}{-\Lambda(k) \frac{\partial V}{\partial \rho_e} (k)} \right)^\eta = \rho_e^{(k)} (A^{(k)})^\eta \quad (10)$$

$$\rho_e^{(k+1)} = \begin{cases} \rho_e^{L(k)} & (\rho_e^{(k)} (A^{(k)})^\eta \leq \rho_e^{L(k)}) \\ \rho_e^{U(k)} & (\rho_e^{(k)} (A^{(k)})^\eta \geq \rho_e^{U(k)}) \\ \rho_e^{(k)} (A^{(k)})^\eta & (\text{otherwise}) \end{cases} \quad (11)$$

$$\rho_e^{L(k)} = \max \{ \rho_e^{(k)} - \varsigma, 0 \} \quad (12)$$

$$\rho_e^{U(k)} = \min \{ \rho_e^{(k)} + \varsigma, 1 \} \quad (13)$$

where ς is the move limit of density, and Λ is Lagrange multiplier. The solution of Lagrange multiplier Λ is found by the bisection method. The SIMP method is often applied to topology optimization based on the density method[4]. In this study, the mass density, damping coefficient and Young's modulus are, respectively, represented by the SIMP method as follows

$$\gamma_e(\rho_e) = (\gamma_0 - \gamma_{min}) \rho_e^{p_m} + \gamma_{min} \quad (14)$$

$$\zeta_e(\rho_e) = (1 - \zeta_{min})\rho_e^{p_c} + \zeta_{min} \quad (15)$$

$$E_e(\rho_e) = (E_0 - E_{min})\rho_e^{p_k} + E_{min} \quad (16)$$

where γ_0 , E_0 , γ_{min} , ζ_{min} , E_{min} , p_m , p_c and p_k are respectively, the mass density of a material, the Young's modulus of a material, the mass density for numerical stability, the damping coefficient for numerical stability, the Young's modulus for numerical stability, the penalization parameter for mass density, the penalization parameter for damping coefficient and the penalization parameter for the Young's modulus. If the value of penalization parameters are changed, the values of sensitivity and physical property are also changed as shown in Figures 2 and 3.

Figure 2: SIMP method.

Figure 3: Gradient of SIMP method.

The mass matrix, damping matrix, and stiffness matrix are written as

$$[M(\rho_e)] = \int_{\Omega} \gamma_e(\rho_e) [N]^T [N] d\Omega \quad (17)$$

Register for free at <https://www.scipedia.com> to download the version without the watermark

$$[C(\rho_e)] = \zeta_e(\rho_e) (\alpha_1 [M_0] + \alpha_2 [K_0]) \quad (18)$$

$$[M_0] = \int_{\Omega} \gamma_0(\rho_e) [N]^T [N] d\Omega \quad (19)$$

$$[K_0] = \int_{\Omega} [B]^T [D(E_e(\rho_e))] [B] d\Omega|_{E_e=E_0} \quad (20)$$

$$[K(\rho_e)] = \int_{\Omega} [B]^T [D(E_e(\rho_e))] [B] d\Omega \quad (21)$$

where $[N]$, $[B]$, $[D]$ and α are, respectively, the shape function, B-matrix, D-matrix and Rayleigh damping.

3 COMPUTATIONAL FLOW

This chapter describes the topology optimization flowchart described in the precious chapter.

Step 1: Input of computational conditions and setting a computational model.

Step 2: 3D linear elastic analysis based on the finite element method is performed to obtain the displacement.

Step 3: The performance function is calculated with the displacement.

Step 4: If the judgment of convergence equation $|J^{(k)} - J^{(k-1)}| < \epsilon$ is satisfied, the computational is finalized. Otherwise, go to the next step.

Step 5: Sensitivity analysis is performed using the gradient of the Lagrange function with respect to density ρ .

Step 6: The density is updated by the OC method. Then go back to step 2.

By setting the maximum number of iterations k_{max} , the computational is finalized even if the judgment of convergence equation is not satisfied.

4 COMPUTATIONAL CONDITIONS

This chapter describes the calculation model and calculation conditions. In this study, the calculation model is the cantilever beam model as shown in Figure 4, the red arrow indicates uniformly distribution load, and the Y-Z surface is fixed in all directions. The load is assumed to be the impulse waveform as shown in Figure 5. The model size is 40 [mm]×10 [mm]×32 [mm], and an element is a cube with a side 1 [mm]. Other common conditions are as shown in Table 1. As mentioned in Chapter 1, in the unsteady oscillation problem for the cantilever beam model, the optimal density distribution is changed by the scale of each sensitivity term. And, in the topology optimization based on the SIMP method, the physical property and sensitivity are defined by penalization parameters. Thus, in this study, comparative studies are conducted when one penalization parameter is changed, as shown in Table 2.

Figure 4: Cantilever model with boundary conditions.

Figure 5: Relationship between load and time.

Table 1: Computational conditions.

Element type	Hexahedron
Number of nodes	14883
Number of elements	12800
Time [s]	0.3
Time increments Δt [s]	5×10^{-6}
Initial density average $\bar{\rho}_0$	0.5
Damping parameter η	0.75
Move limit of density ζ	0.15
Convergence criterion of performance function ϵ	10^{-7}
Maximum number of iterations k_{max}	100
Mass density γ_0 [kg/mm ³]	7.86×10^{-6}
Young's modulus E_0 [GPa]	206
Poisson's ratio ν	0.3
Rayleigh damping α_1, α_2	90, 10^{-5}
Mass density for numerical stability γ_{min} [kg/mm ³]	10^{-10}
Damping coefficient for numerical stability ζ_{min}	10^{-10}
Young's modulus for numerical stability E_{min} [GPa]	10^{-6}

Table 2: Penalization parameter conditions.

	p_m	p_c	p_k
Case 1	3.0	3.0	3.0
Case 2	6.0	3.0	3.0
Case 3	3.0	6.0	3.0
Case 4	3.0	3.0	6.0

Register for free at <https://www.scipedia.com> to download the version without the watermark

5 RESULTS OF NUMERICAL ANALYSIS

In this chapter, the results of topology optimization analysis in unsteady oscillation problem for the cantilever beam model are described. Figures 6 to 9 show the results of density distribution. Here, the elements with a density of 0.2 or less are eliminated. The left view of these figures represents an isometric view, and the right view represents a side view. In addition, Figure 10 shows the displacement waveform in Z direction at the load point, and Figure 11 and Table 3 show the performance function history and the value of performance function at the convergence, respectively. First, from the results of the density distribution, different density distributions were obtained by changing the penalization parameters, p_m , p_c and p_k . However, there is no big difference. The density distributions of Cases 1 and 2 are like a solid. In contrast, the density distributions of Cases 3 and 4 are like a hollow. Comparing the side views of Cases 1 and 2, it can be seen that the side view of Case 2 has a lot of density distribution at the tip. The result of Case 4 has the most density distribution at fixed end of all Cases. Next, the results of the displacement waveform and performance function are described. If the penalization parameters are changed, the displacement waveform and performance function are smaller than the result of Case

1. In particular, the result of Case 4 has the smallest displacement waveform and performance function. On the other hand, the performance functions of Cases 1 and 3 have almost the same value. With these results in mind, we found two points. The first point is that the results of the smallest displacement waveform and performance function can be obtained by increased the penalization parameter p_k . The second point is that the displacement waveform and performance function do not improve even if the penalization parameter p_c is increased.

Figure 6: Density distribution at convergence in Case 1.

Figure 7: Density distribution at convergence in Case 2.

Figure 8: Density distribution at convergence in Case 3.

SCIPEDIA

Register for free at <https://www.scipedia.com> to download the version without the watermark

Figure 9: Density distribution at convergence in Case 4.

Figure 10: Displacement waveform in Z direction.

Figure 11: Performance function history.

Table 3: Penalization parameter conditions and converged performance function.

	p_m	p_c	p_k	Performance function J [J]
Case 1	3.0	3.0	3.0	2.25×10^{-5}
Case 2	6.0	3.0	3.0	2.19×10^{-5}
Case 3	3.0	6.0	3.0	2.24×10^{-5}
Case 4	3.0	3.0	6.0	2.16×10^{-5}

6 CONCLUSION

This paper is written the unsteady oscillation problem in topology optimization for a cantilever beam model. The first study was divided the optimization problem into maximization problem and minimization problem by classified the strain energy into the work in the positive and the work in the negative. Thereby, the self-adjoint relationships were derived. The second study was investigated the relationship between each sensitivity term and the result of topology optimization. Sensitivity was classified into three terms, and the ratio of each sensitivity was changed by changing the penalization parameters of the SIMP method. As a result, the displacement waveform and performance function were the smallest when the penalization parameter p_k was increased. In contrast, when the penalization parameter p_c was increased, the results were not much different from when the penalization parameters were the same. Therefore, it was found that the sensitivity of the stiffness matrix $[K]$ is the most important when the strain energy is used as the performance function.

ACKNOWLEDGMENTS

This work was supported by Grant-in-Aid for Scientific Research (C) Grant No. 18K03897 and funds for joint research from Oiles Corporation. Most of the topology optimization was carried out using the supercomputer system at Kyushu University's Institute for Information Technology. We wish to thank all the persons who assisted us in this study.

REFERENCES

- [1] Bendsøe M. P. and Kikuchi N., Generating optimal topologies in structural design using a homogenization method, *Comput. Methods in Appl. Mechanics and Eng.*, (1988) **71**:891–909.
- [2] Bendsøe M. P. and Sigmund O., Topology optimization: Theory, Methods and Applications, *Springer-Verlag Berlin Heidelberg GmbH*, (2003).
- [3] Suzuki K. and Kikuchi N., A homogenization method for shape and topology optimization, *Comput. Methods in Appl. Mechanics and Eng.*, (1991) **93**(3):291–318.
- [4] Bendsøe M. P. and Sigmund O., Material interpolation scheme for minimum compliance topology optimization, *Archive of Appl. Mechanics*, (1999) **69**(9):635–654.

Register for free at <https://www.scipedia.com> to download the version without the watermark