STRUCTURAL MEMBRANES 2021, TU München, 13-15 September 2021:
Fluid-Structure Interaction of a 3D Finn Dinghy Sail Membrane with Surrounding Viscous Air Flow
Carsten Corte

Baustatik – Baudynamik – Numerische Modellierung
Thrasoltstraße 12, 10585 Berlin, Germany
Tel. : +49-(0)30-347 871 78, Fax: +49-(0)30-347 871 80, pfeifercorte@t-online.de

ABSTRACT (DATE OF SUBMISSION: MARCH 15, 2021)
(SESSION: NUMERICAL METHODS AND MODELING FOR LIGHTWEIGHT STRUCTURES)

Structural mechanics and dynamics of membrane structures are based on the in-plane tangential tensile force equilibrium of curved elastic surface structures.

Sailing dinghies are lightweight structures that gain drive by main sail membrane with surrounding air flow. A finn class rules conform plane finn sail with plane curved boundaries is considered.

In a first step, stress-free transformation of the plane finn sail membrane with plane curved boundaries into two different warped configurations to meet beam elastic straight mast at luff and beam elastic boom at foot are determined as two different initial configurations to start finite element modeling of membrane time domain analysis. Structural elastic mast and structural elastic boom are equal-displacement connected to sail luff membrane boundary and sail foot membrane boundary, respectively. Structural boom is joint-connected to structural mast and translational-spring-connected to floor. Structural mast is horizontal-displacement fixed at deck height and fully displacement fixed at mast bottom.

In a second step, translational-spring-connection of boom to floor is spanned to model tightening of the sheet. This membrane-stress inducing transformation is performed from the two different initial stress-free warped membrane configurations and gives large 3D membrane displacement and membrane stress distribution, large 3D mast and boom beam displacement and rotation and 3D mast and boom beam section forces, furthermore floor, mast-at-deck-height and mast bottom support reaction forces.

In a next step, using deformed stress-carrying membrane and beam state as above, surrounding viscous air flow is modeled by Navier-Stokes equations for light wind, average wind, strong wind conditions on close reach in time domain.

In a final step, strong segregated fluid-structure interaction between sail membrane with added mast and boom beam stiffness and viscous air flow is performed in time domain. Flow state around the sail membrane, membrane, mast and boom deformation, membrane stress and mast and boom beam section forces, floor, mast-at-deck-height and mast bottom reaction forces and resulting driving forces and heeling moment that act onto the hull are evaluated.

sail measurement [finn class rules] plane sail shape, curved boundaries 1st warped stress-free configuration 2nd warped stress-free configuration

REFERENCES

- [1] C. Corte, “3D membrane theory”, 11th WCCM, Barcelona, **268-292**, 2014.
- [2] C. Corte, “3D Membrantheorie”, Stahlbau 83, Heft 5, **343-358**, Ernst und Sohn Verlag, 2014.
- [3] C. Corte, “Membrane roof structures”, STRUCTURAL MEMBRANES 2017, Technische Universität München, **478-502**, 2017.
- [4] K.-U. Bletzinger, “Formfindung von leichten Tragwerken” in Baustatik-Baupraxis (Hrsg. D. Dinkler), **99-110**, Institut für Statik, Technische Universität Braunschweig, 2002.
- [5] C. Corte, J. García, E. Oñate, “Three-dimensional flow around rigid and elastic cylindrical structures”, **32 pages**, CIMNE Barcelona, 2007.
- [6] C. Corte, J. García, E. Oñate, “A strongly coupled segregated approach for finite element modeling of fluid-structure interaction”, **17 pages**, CIMNE Barcelona, 2008.
- [7] C. Corte, “A segregated approach for strong coupling of finite element solvers to model fluid-structure interaction”, **30 pages**, CIMNE Barcelona, 2008.
- [8] C. Corte, “A 3D approach for finite element modeling of viscous fluid flow”, **24 pages**, Dr. C. Corte, Baustatik—Baudynamik—Numerische Modellierung, Berlin, Tel. / Fax +49-(0)30-347 871 78 / 80, 2010.
- [9] C. Corte, “A 3D approach for finite element modeling of fluid-structure interaction between incompressible viscous fluids and elastic structures”, **64 pages**, Dr. C. Corte, Baustat.—Baudyn.—Num. Modell., Berlin, Tel./Fax+49-(0)30-347871-78/80, 2011.
- [10] C. Corte, “Finite element modeling of fluid-structure interaction for an elastic 2D flag in harmonic viscous flow and an elastic 3D sail structure in stationary viscous fluid flow”, **39 pages**, Dr. C. Corte, Baustatik—Baudynamik—Numerische Modellierung, Berlin, Tel. / Fax +49-(0)30-347 871 78 / 80, 2012.