

AVERAGING TECHNIQUES FOR MICROSTRUCTURES WITH LOCALIZATION BANDS DUE TO DAMAGE PROGRESSION

L. Poggenpohl^{1*}, J.-W. Simon¹

¹ Institute of Applied Mechanics, RWTH Aachen University, Mies-van-der-Rohe-Str. 1, 52074 Aachen, Germany

* lukas.poggenpohl@ifam.rwth-aachen.de

Despite the complex manufacturing process and the relatively high manufacturing costs involved, the use of carbon fiber reinforced plastics (CFRP) is constantly increasing in lightweight constructions. However, due to their brittle damage behavior, high safety factors are required to prevent catastrophic failure. More insight into the microscopic failure mechanisms is needed. Multiscale analysis of representative volume elements (RVEs) can provide insight into the microscopic material behavior and failure mechanisms.

However, standard first order homogenization schemes based on the so-called Hill condition [1] fail in the presence of localization bands, because a representative size of the RVE cannot be identified [2]. In order to overcome this problem, Nguyen et al. [3] have proposed the so-called failure zone averaging scheme, which allows the definition of a representative RVE-size even after localization bands have occurred.

In the current work, this approach is adopted to provide micro-scale simulations of the microscopic failure of CFRPs. Here, the matrix material is equipped with a micromorphic brittle damage model, while cohesive zone elements are used to simulate the interface debonding of carbon fibers and resin matrix. Results using the failure zone averaging for various microstructures and different external loadings will be presented and discussed.

References

- [1] Hill, R. (1967) , ‘The essential structure of constitutive laws for metal composites and polycrystals’, *Journal of the Mechanics and Physics of Solids* **15**(2), 79–95.
- [2] Gitman, I., Askes, H. and Sluys, L. (2007) , ‘Representative volume: Existence and size determination’, *Engineering Fracture Mechanics* **74**(16), 2518 –2534.
- [3] Nguyen, V. P. and Lloberas-Valls, O. and Stroeven, M. and Sluys, L. J (2010) , ‘On the existence of representative volumes for softening quasi-brittle materials - a failure zone averaging scheme’, *Computer Methods in Applied Mechanics and Engineering* **199**(45), 3028 – 3038.