Decision Support to Identification of Road Infrastructure Segments With Poor Conditions

Nikša Jajac

Faculty of Civil Engineering, Architecture and Geodesy, University of Split, Matice hrvatske 15,
21214 Split, Croatia, niksa.jajac@gradst.hr

Abstract. *Planning of maintenance activities (an integral approach) on ever growing system such as urban road infrastructure requires decision makers to take into account large number of different data and usually conflicted criteria, derived from several aspects of analysed problem. This systematic approach to planning is based on the main three steps: identification of alternatives, their validation and selection for inclusion into a maintenance plan. Most of authors are dealing with the last two steps however, focus of this research is on the first step. This step is a critical phase of planning because it is important to identify road infrastructure segments that need to be improved. Meaning, those with poor condition. The condition of a segment must be expressed as simple as possible (by unique Condition Assessment Value) and by usage of few but most relevant criteria (such as level of service, safety, time period passed form the last renovation and stability). Another important issue is provision of relevant, relatively quick and consistent expert assessment of segment condition according to above mentioned criteria and for large number of segment. To insure such assessment with high quality of segments identification this paper propose an decision support concept/expert system based on combination of trained and tested Artificial Neural Networks (ANN) and Simple Additive Weighting (SAW) method. The concept is validated on urban road infrastructure of city centre of Split, Croatia and it proved to be useful for determining a set of road infrastructure segments where maintenance activities should be undertaken.*

Keywords: *Decision Support Concept, Road Infrastructure Segments, Planning, Artificial Neural Networks.*

1 Introduction

In the field of urban road infrastructure systems, planning process of maintenance activities is highly complex and ill structured problem. This complexity is defined by several factors: lots of stakeholders with different opinions, huge amount of information quantities, multidisciplinary character of the problem, conflicts among goals and criteria, budget restrictions, etc. These factors indicate that the decision-making to maintaining activities of the road infrastructure planning are burdened with complex and socially sensitive problems, especially for the long-term planning. For that reason, long-term planning tasks should be supported by decision making tools such are multicriteria methods that can contribute to a more efficient realization of the tasks. In order to manage such complexity, a decision support approach is proposed, aimed at improving decision making to planning of maintain activates at the road infrastructure system. This concept represents a multicriteria decision-making approach, and is based on multicriteria analysis. Three main steps are crucial for a realization of planning: identification of alternatives, their validation and selection for inclusion into a maintenance plan. In this research, focus is given to the first step where road infrastructure

segments are identified and need to be improved because of their poor condition. These conditions are expressed by Condition Assessment Value (CAV), using few the most relevant criteria (such as level of service, safety and time period passed from the last renovation, etc.).

Expert assessment of segments conditions according to defined criteria are given and to achieve the most precise assessment this paper propose an decision support concept and expert system based on combination of trained and tested Artificial Neural Networks (ANN) and Simple Additive Weighting (SAW) method. There are many studies dealing with possibilities of generating decision support tools for maintaining road infrastructure segments. Zavadskas, Liias and Turskis (2008) gave a review of international and national practices in investment decision support tools in bridges and road quality management. He, Song and Chaudhry (2013) in their paper, explored the integration problem of service-oriented system and intelligence technology through the use of a group decision support system, applied on transportation management. Petty and Mahoney (2008) gave enhancements and refinements associated with winter maintenance decisions that the United States Federal Highway Administration initiated in a project aimed at developing a winter road Maintenance Decision Support System (MDSS).

The goals of the MDSS project were to construct a functional prototype MDSS that can provide objective guidance to winter road maintenance decision makers concerning the appropriate treatment strategies. These strategies are used to control roadway snow and ice during adverse winter weather events, and develop a prototype that will also serve as a catalyst for additional research and development by the private sector. Dunkel *et al.* (2011) proposed a reference architecture for event-driven traffic management systems, which enables the analysis and processing of complex event streams in real-time and is therefore well-suited for decision support in sensor-based traffic control systems. Zhou *et al.* (2010) presented a research effort undertaken to explore the applicability of data mining and knowledge discovery (DMKD) in combination with Geographic Information System (GIS) technology to pavement management to better decide maintenance strategies, set rehabilitation priorities, and make investment decisions. Bielli (1992) presented a decision support system to urban-traffic management to

Register for free at <https://www.scipedia.com> to download the version without the watermark

enhance efficiency and productivity for the existing traffic system, including the urban road infrastructure. Guisseppi and Forgione (2002) and Jajac, Knezić and Marović (2009) in their papers gave a cost and benefit aspect of potential infrastructure investments, showing that several decision-support models can be generated. Quintero, Konaré and Pierre (2005) described an improved decision support system named Intelligent Decision Support System that coordinates management of several urban infrastructure systems, such as the sewage and waterworks. Proposed Intelligent Decision Support System was a solution for the future urban infrastructure management. Similar approaches were given by Pomerol, Roy and Rosenthal-Sabroux (1996), Turban and Aronson (1995) and Leclerc *et al.* (2001). Sayers, Jessop and Hills (2003) used SAW method (Hwang and Yoon, 1981) to present a multicriteria evaluation of transport infrastructure for ranking transport investments. These investments aim was to improve infrastructure in small towns, analysing three solutions: minimum interventions on the existing network, upgrading the existing route, and building a bypass. A simplified transport project ranking methodology with an integrated multicriteria decision making process that prioritizes transport projects in cases when multiple stakeholders present various different opinions was given by Shelton and Medina (2010) and Jajac, Marovic and Baucic (2014). Jajac (2010) made a research on the development and maintenance of urban road infrastructure by implementing and using multicriteria analysis and ANN at strategic, tactical and operating

decision making levels, in urban areas. To improve a decision making process in such complex circumstances, it is important to develop new tools aimed at raising the level of transparency and objectivity in the solution-selection process (Jajac, 2010). This research is focused on decision support concept to maintenance activities planning of improving road infrastructure segments in urban areas. It is based on the multicriteria methods AHP and SAW, and expert systems, using ANN, to support project management. The concept is validated on the urban road infrastructure of the city centre of Split, Croatia, and proved to be useful for determining a set of road infrastructure segments where maintenance activities should be undertaken.

2 Decision Support to Improve Maintenance Planning of Road Infrastructure Segments

Using architecture of the DSS for urban-infrastructure management (Jajac, 2010), a decision support to planning of maintenance activates improvement of road infrastructure segments is developed. The model for improving urban road infrastructure segments maintenance planning is proposed in Figure 1. The process of decision-making starts at the strategic and tactical levels, where with the case study is determined and stakeholders are selected. The main characteristics of each segment of infrastructure are collected and stored in database, they are accessible for entering periodically new inputs at the operational level during the continuous maintenance process. These main characteristics of segments are important for defining criteria and their weights. Firstly, stakeholder are selected and gathered together through subjective assessment of their influence and legitimacy. They are divided into three groups:

Local government - deputy mayor who is responsible for utility affairs, and principals of several administrative offices (e.g. Office for Strategic Planning and Development, Office for Finance, Office for Physical Planning, etc.);

Experts - civil engineering, transport engineering, environmental, and economics experts of both academic and practical backgrounds;

Users - the representatives of city districts or similar city formations.

After the identification of stakeholders, goals, criteria, and weighting factors are defined. The goal analysis is given in the form of hierarchical structure of goals and criteria. The criteria are defined by local government and experts group, while criteria weights are determined by all stakeholder groups. Using the AHP method (Saaty, 1982) and interviewing all stakeholders, weights can easily be assigned through a group decision-making process. The decision-making process of each stakeholder group must be repeated until consistency of each group' criteria weights determination is achieved. Furthermore, having determined the hierarchy of goals and stakeholder groups, three scenarios are developed, while the final (fourth) scenario is determined as the compromise opinion of all groups. Values of the compromise opinion are introduced as weights for the SAW method, which is used to set priority of selected road segments according to their improvement requirements. After the goal hierarchy is defined, all segments are analyzed, and those with conditions that need to be improved are identified using ANN. This way the condition assessment for all segments is provided within the study area. Only those segments with the condition assessed as poor, unsuitable and worn-out are selected for further analysis and priority-setting. Moreover, the segments are then ranked according to defined criteria. The local-government representatives, as strategic decision-makers, assisted to the group of experts in selecting the most convenient solution based on the present policies and

Register for free at <https://www.scipedia.com> to download the version without the watermark

multicriteria analysis. The selected solution establishes a strategic plan of the road infrastructure segments conditions improvement. The proposed concept was tested on the road infrastructure segments maintenance planning in the city of Split, Croatia.

Figure 1. Decision support to road infrastructure segments improvement.

Register for free at <https://www.scipedia.com> to download the version without the watermark

3 Road Infrastructure Segments Improvement Planning

The city of Split is taken as a study area. It has a high concentration of public facilities and pedestrian flows. There were 236 identified infrastructure segments, divided into 10 types: street, street section, crossroad, garage, parking, bus station, bus terminal, petrol station, overpass and tunnel. To evaluate each of the elements 13 criteria are defined. Each group of stakeholders defined criteria in their field of expertise. These criteria are grouped in social, technical, economic and ecologic group, as is shown in Table 1. Three scenarios are created, one for each stakeholders' groups and each for each scenario criteria weights are determined using AHP method. Compromise scenario is calculated as average value of each criterion weight by each scenario. Using compromise scenario, opinions of all three groups are equally taken into account.

Table 1. Criteria definition with weights and scenarios.

Group of criteria	Criteria name	Criteria label	Scenario 1	Scenario 2	Scenario 3	Compromise scenario
Social	Population density	C1	0.05	0.03	0.06	0.05
	Density of business facilities	C2	0.06	0.04	0.04	0.05
	Area of business facilities	C3	0.04	0.01	0.02	0.03
	Density of public facilities	C4	0.03	0.02	0.05	0.03
	Constructability	C5	0.06	0.09	0.08	0.08
Technical	Fitting into plans	C6	0.09	0.08	0.09	0.09
	Maintenance-segment improvement	C7	0.10	0.12	0.08	0.10
	Functionality improvement	C8	0.09	0.12	0.08	0.09
	The amount of investment	C9	0.08	0.10	0.11	0.10
Economic	The ability of land buying	C10	0.09	0.09	0.11	0.10
	The existence of investor	C11	0.09	0.09	0.10	0.09
	The amount of noise	C12	0.10	0.11	0.08	0.10
Ecologic	The amount of combustion gasses	C13	0.11	0.11	0.10	0.10

Register for free at <https://www.scipedia.com> to download the version without the watermark

Criterion C7 (Maintenance – segment improvement) is divided into four subcriteria: level of service, safety, time period passed form the last renovation and stability. Using these four subcriteria and methodology of ANN, the unique Condition Assessment Value (CAV) is obtained. This value also presents an assessment of condition of segment.

4 Results

Using methodology of ANN, road-infrastructure segments in poor conditions are identified, by including four input variables and only one output variable. The four input variables are four criteria defined in previous section: level of service, safety, time period passed form the last renovation and stability. This ANN is trained by the back-propagation algorithm using the training set consisting of 200 cases, each case with four input variables (collected during the monitoring cycle), and 200 output variables, provided by experts' assessment. The output variable is CAV. Input values for 236 segments are collected during the second monitoring

cycle. Applying ANN methodology, conditions of segments are obtained. However, only segments assessed as inadequate and poor were selected for further analysis. If the CAV is less than 1, condition is classified as bad (0-worst condition, 1-the best condition). Segments with CAV values are shown in Table 2. There are 18 segments with poor condition, and the best one is segment Sg13 (crossroad), while the worst is Sg8 (street section).

Table 2. Road infrastructure segments with poor condition.

Infrastructure segment	Label of segment	CAV
Street section (Pojišanska 1)	Sg1	0.458
Street section (Pojišanska 2)	Sg2	0.634
Crossroad (Pojišanska i Zvonimirova)	Sg3	0.556
Street (Put Stinica)	Sg4	0.543
Street section (Sukoišanska)	Sg5	0.687
Crossroad (Meštrovićeva, Sustipanskog P. and Ulica Dražanac)	Sg6	0.731
Crossroad (Spinčičeva, Zajčeva and Put Firula)	Sg7	0.476
Street section (Ulica slobode)	Sg8	0.437
Garage (Varoš 4)	Sg9	0.489
Crossroad (Hercegovačka, Put suplava and Put stinica)	Sg10	0.685
Crossroad (Sukoišanska and Starčevićeva)	Sg11	0.577
Street section (Domovinskog rata)	Sg12	0.496
Crossroad (Kavanjinova, Manderova)	Sg13	0.832
Garage (Spinut North 4)	Sg14	0.747
Bus station (Pojišanska 2)	Sg15	0.659
Garage (Lovret North 1)	Sg16	0.671
Crossroad (Mažuranićevo Š., Dom. rata and Gundulićeva)	Sg17	0.681
Crossroad (Vukovarska, Bihaćka, Zagrebačka and Dom. rata)	Sg18	0.729

Register for free at <https://www.scipedia.com> to download the version without the watermark

Table 3 shows the ranking of the infrastructure segments. Criteria weights values are calculate from the compromise scenario. These weight values are then used in the SAW method. Segments are evaluated by experts. Evaluations are normalized and transformed, and then SAW is included in further process. All of 13 criteria are used for evaluation of 18 infrastructure segments. Table 3 shows the ranking of 18 segments. The segment evaluation with higher score value means that the segment is considered as prior to improvement. In this case segment Sg10 (76.87) has the highest value, while the Sg8 (25.88) has the lowest.

Table 3. Ranking of segments.

Segment label	Score	Rank position	Segment label	Score	Rank position
Sg1	70.32	7.	Sg10	76.87	1.
Sg2	72.75	4.	Sg11	54.12	11.
Sg3	71.58	6.	Sg12	49.16	14.
Sg4	44.35	15.	Sg13	38.67	17.
Sg5	73.28	3.	Sg14	66.57	8.
Sg6	58.21	10.	Sg15	53.41	12.
Sg7	40.13	16.	Sg16	63.18	9.
Sg8	25.88	18.	Sg17	72.45	5.
Sg9	73.31	2.	Sg18	49.82	13.

With proposed model of decision support, ranking list for the priority of improvement of infrastructure segments is obtained as is shown in Table 3. Then local-government representatives selected the most appropriate solution, according to the results of the ranking and present policies. The selected solution must be in consent with financials available in the budget of city of Split. Finally, eight top-ranked segments are included in the maintenance plan, in the next investment period.

5 Conclusions

- In this paper an approach of decision support for the road infrastructure segments maintenance planning is proposed. With this approach, support to final decision maker, in this case to local government of city of Split, can be very useful and practical, especially in making decisions for the compound and ill-structured problem such as maintenance planning of the road infrastructure segments. One of the main characteristics of the approach is analysis of required data and selection of appropriate methods.
- The proposed approach is used for obtaining the priority ranking of the infrastructure segments. Relevant stakeholders are identified and gathered together to determined criteria that are used for segments evaluation. Stakeholders were divided into three groups: local government, experts, and users, and were directly involved in the decision-making process, expressing their opinions through criteria weights, using AHP and SAW method.
- This approach is a combination of multicriteria analysis and ANN. Monitoring the infrastructure segments using relevant criteria such are level of service, safety, time period passed form the last renovation and stability, data were collected that were further introduced into the ANN methodology. This way, condition evaluations of infrastructure segments are obtained as values of CAV. Involving ANN methodology as a knowledge-based system, substitution of experts can be achieved.
- The presented approach of decision support is an adequate tool for decision makers in the field of the improvement of maintenance planning of road-infrastructure segments.

Acknowledgements

This research is partially supported through project KK.01.1.1.02.0027, a project co-financed by the Croatian

Government and the European Union through the European Regional Development Fund–the Competitiveness and Cohesion Operational Programme.

ORCID

Nikša Jajac: <https://orcid.org/0000-0003-2218-6507>

References

- Bielli, M. (1992). *A DSS approach to urban traffic management*, *European Journal of Operational Research*, 61(1-2), 106-113.
- Deluka-Tibljaš, A., Karleuša, B., and Dragičević, N. (2013). *Review of multicriteria-analysis methods application in decision making about transport infrastructure*. *Građevinar*, 65(7), 619-631.
- Dunkel, J., Fernandez, A., and Ortiz, R. et al. (2011). *Event-Driven Architecture for Decision Support in Traffic Management Systems*. *Expert systems with applications*, 38(6), 6530-6539.
- Guisseppi, A., and Forgionne, G.A. (2002). *Selecting rail grade crossing investments with a decision support system*. *Information Sciences*, 144(1-4), 75-90.
- He, S., Song, R., and Chaudhry, S.S. (2014). *Service-oriented intelligent group decision support system: Application in transportation management*. *Information Systems Frontiers*, 16 (5), 939-951.
- Hwang, C.-L., and Yoon, K. (1981). *Multiple Attribute Decision Making: Methods and Applications - A State-of-the-Art Survey*. Springer-Verlag, New York.
- Jajac, N. (2010). *Modeling of the decision support systems for urban road infrastructure development and maintenance*. Dissertation, University of Split, Faculty of Economics, Split, Croatia.
- Jajac, N., Knezić, S., and Marović, I. (2009). *Decision support system to urban infrastructure maintenance management*. *Organization, Technology and Management in Construction – An International Journal*, 1(2), 72-79.
- Jajac, N., Marović, I., and Baucic, M. (2014). *Decision support concept for managing the maintenance of city parking facilities*. *Electronic journal of the Faculty of Civil Engineering Osijek-E-GFOS*, 9, 60-69.
- Leclerc, G., Hmiya, S., Aïmeur, E., Quintero, A., Pierre, S., and Ochoa, G. (2001). *An intelligent decision support system (IDSS) for an urban infrastructure complaint management module*. *World Multiconference on Systemics, Cybernetics and Informatics, ISAS/SCI 2001, Orlando, Florida, vol. XVIII*, pp. 143–147.
- Petty, K.R., and Mahoney, W.P. (2008). *The U.S. Federal Highway Administration winter road Maintenance Decision Support System (MDSS): Recent enhancements & refinements*. *Sirwec, Prague*, 14-16 May, 29: 1-12.
- Pomerol, J., Roy, B., and Rosenthal-Sabroux, C. (1996). *Development of an "intelligent" system for the evaluation of railway timetables: Problems and issues*. *Journal of Decision Systems*, 5, 249–267.
- Quintero, A., Konaré, D., and Pierre, S. (2005). *Prototyping an intelligent decision support system for improving urban infrastructures management*. *European Journal of Operational Research*, 162(3), 654–672.
- Saaty, T.L.: *Decision Making for Leaders, The Analytic Hierarchy Process for Decisions in a Complex World*, Wadsworth, Belmont, 1982.
- Sayers, T.M., Jessop, A.T., and Hills, P.J. (2003). *Multi-criteria evaluation of transport options-flexible, transparent and user-friendly?*, *Transport Policy*, 10(2), 95-105.
- Shelton, J., and Medina, M. (2010). *Integrated multiple-criteria decision making method to prioritize transportation projects*. *Transportation Research Record: Journal of the Transportation Research Board*, 2174, 51-57.
- Turban, E., and Aronson, J.E. (1995). *Decision Support Systems and Intelligent Systems*. 5th edition, Simon and Schuster Company, Upper Saddle River, NJ.
- Zavadskas, E.K., Liias, R., and Turskis, Z. (2008). *Multi-attribute decision-making methods for assessment of quality in bridges and road construction: state-of-the-art surveys*. *The Baltic journal of road and bridge engineering*, 3(3), 152–160.
- Zhou, G., Wang, L., Wang, D., and Reichle, S. (2010). *Integration of GIS and Data Mining Technology to Enhance the Pavement Management Decision Making*. *Journal of Transportation Engineering*, 136(4), 136:332-341.

Register for free at <https://www.scipedia.com> to download the version without the watermark