All-hexahedral mesh smoothing with a node-based measure of quality

N. A. Calvo and S. R. Idelsohn^{*,†}

Centro Internacional de Métodos Computacionales en Ingeniería - CIMEC, Güemes 3450, (3000) Santa Fe, Argentina

SUMMARY

This research work deals with the analysis and test of a normalized-Jacobian metric used as a measure of the quality of all-hexahedral meshes. Instead of element qualities, a measure of node quality was chosen. The chosen metric is a bound for deviation from orthogonality of faces and dihedral angles. We outline the main steps and algorithms of a program that is successful in improving the quality of initially invalid meshes to acceptable levels. For node movements, the program relies on a combination of gradient-driven and simulated annealing techniques. Some examples of the results and speed are also shown. Copyright © 2001 John Wiley & Sons, Ltd.

KEY WORDS: unstructured mesh; hexahedral mesh; smoothing; Jacobian metric; all-hexahedral mesh

1. INTRODUCTION

The optimization of a given mesh for Finite Element Analysis implies that the elements must satisfy certain quality conditions. Many methods are currently in use [1–3] and there is also an excellent compendium of matrix norms useful for hexahedra, cited in Reference [4], but it is still difficult to give a concrete meaning to the word ‘quality’ for a mesh.

Even though the actual algorithm we use combines orthogonality with aspect ratio, we will only concentrate here on the angular aspect of quality. This is because traditional methods give us meshes with negative-angled elements. Therefore, within the scope of this paper, any hexahedral element must have its edges and faces as orthogonal as possible.

We will be using the term ‘Jacobian’ for the matrix involved in the mapping between any tetrahedron over the canonical one. A tetrahedral element can be mapped with a single Jacobian matrix whereas hexahedral elements have a different Jacobian at each vertex.

Mesh improvement involves two main approaches, which are sometimes used together: smoothing and topological operations. It is a common practice to use the term ‘smoothing’ when only changes in node positions are involved. When there are some changes in the connectivity among

^{*}Correspondence to: S. R. Idelsohn, CIMEC, Güemes 3450, 3000 Santa Fe, Argentina

[†]E-mail: rnsrqio@alpha.arcrude.edu.ar

Figure 1. A trihedron in a hexahedral mesh element.

Figure 2. Dependence of two-dimensional metric on the node position, for one of the elements attached to the moving node.

the nodes, changing also the quantities of nodes or elements, these operations are referred to as topological changes.

Whereas tetrahedral meshes can readily undertake local topological changes, they are still unimplemented for all-hexahedral meshes. This is because of the lack of algorithms to handle and operate with dual surfaces or sheets of elements [5–7]. We are currently smoothing, i.e. repositioning nodes without changing the topology of the mesh.

Until recently, the only known smoothing technique applied to hexahedra was the Laplacian smoothing [8], a movement of each node towards the centroid of its neighbouring nodes. The drawback of the Laplacian method is the compression and even inversion (negative Jacobian) of elements near concave areas of the boundary. Even the newest methods [3, 4] cannot successfully untangle a mesh with inverted hexahedral elements.

register for free at <https://www.scipedia.com> to download the version without the watermark

2. THE GEOMETRY

2.1. Metric

We are using a technique known as ‘optimization-based smoothing’ [1, 9], where each selected node is moved in order to maximize a quality-related function called quality metric.

The algorithm is intended to move nodes; therefore, instead of handling element qualities, we have defined a node quality metric. The subtle difference between node and element quality has proven useful at the implementation stage. It is easier to evaluate the impact of each movement on the quality of neighbouring nodes using a node-based quality measure.

In order to improve meshes with some concave elements (with a negative Jacobian), we need a metric pushing the mesh towards (positive) orthogonality. After we tested dihedral angles and edge angles as objective functions, we realized that the normalized Jacobian was a simple bound for both of them.

As elements define a trihedron on each node, we will deal mostly with trihedra rather than elements.

Figure 1 shows a mesh element. The segments PA, PB and PC define a trihedron with P as its vertex.

The intersection of S_P^2 (the unit sphere centered at P) and the element is the unit spherical triangle shown greyed. S_P^2 intersects the edges at A_1 , B_1 and C_1 , with $\mathbf{a}$, $\mathbf{b}$ and $\mathbf{c}$ the respective unit vectors so defined.

The angle between the edges PB and PC was labelled $\hat{a}_e$, $\hat{a}_d$ is the dihedral angle between the triangles BPA and CPA; and θ_a is the angle between the edge PA and the normal $\mathbf{b} \times \mathbf{c}$ to the triangle BPC. The letters a, b and c can be cyclically used for all the angles between faces and edges.

In order to avoid any problem with the signs, we choose angles such as $\hat{a}_e$ and $\theta_a \in [0, 180^\circ)$ and dihedrals such as $\hat{a}_d \in (-180^\circ, 180^\circ]$. Thus, when the trihedron becomes inverted, all the θ 's are over 90° and all the dihedrals are negative.

The mapping of these unit vectors in the canonical tetrahedron is made with a Jacobian matrix whose determinant is $j = (\mathbf{a} \ \mathbf{b} \ \mathbf{c})$. It can take values between -1 and 1 , and is the normalized version of the Jacobian determinant $J = (\mathbf{PA} \ \mathbf{PB} \ \mathbf{PC})$ for the element edges.

The normalized Jacobian is an orthogonality measure for each trihedron at P. This measure is a lower bound on the sine of the angle between edges:

$$j = (\mathbf{a} \ \mathbf{b} \ \mathbf{c}) = \mathbf{a} \cdot (\mathbf{b} \times \mathbf{c}) = \cos(\theta_a) \sin(\hat{a}_e) \leq \sin(\hat{a}_e) \quad (1)$$

The dihedral angle $\hat{a}_d$ is the angle between $\mathbf{a} \times \mathbf{b}$ and $\mathbf{a} \times \mathbf{c}$, as seen from A to P, then

$$\sin(\hat{a}_d) = \frac{(\mathbf{a} \times \mathbf{b}) \times (\mathbf{a} \times \mathbf{c}) \cdot \mathbf{a}}{\|\mathbf{a} \times \mathbf{b}\| \|\mathbf{a} \times \mathbf{c}\|} = \frac{(\mathbf{a} \ \mathbf{b} \ \mathbf{c}) \|\mathbf{a}\|}{\|\mathbf{a} \times \mathbf{b}\| \|\mathbf{a} \times \mathbf{c}\|} = \frac{(\mathbf{a} \ \mathbf{b} \ \mathbf{c})}{\sin(\hat{c}_e) \sin(\hat{b}_e)} \geq (\mathbf{a} \ \mathbf{b} \ \mathbf{c}) = j \quad (2)$$

where double bars mean that the module of the enclosed vector was taken. This equation shows the given metric as a lower bound for the sine of the dihedral angles.

As the previous equations are equally applied to the angles on the other edges: the angles between faces and between edges of a trihedron are closer to 90° than the arcsine of j .

We now have a metric to quantify the quality: The quality of a node is the least-valued j from the set of trihedra sharing that node. The quality of the mesh is the worst node quality.

Frequently, some sort of mean value is used instead of the worst one, relations between inner and outer spheres or something alike. These values may be suitable for triangles or tetrahedrons, but are rather dangerous for quads and hexes. They are prone to give inverted elements, and a single one makes the whole mesh useless.

2.2. Internal nodes

In order to improve the quality of a node, we move it while keeping the adjacent ones fixed. With the exception of a few special points, j is a differentiable function of node position. The element to which the worst j belongs, changes as the node moves.

In the two-dimensional (plane) case, we can easily show that problem. In Figure 2, we have isolated one of the quads sharing some node P, and showed the non-adjacent (and irrelevant) edges in dotted lines.

Fixing nodes A and B while P moves in the plane, we can plot j as a function of the position of the moving node. In this case, j is the component of $\mathbf{a} \times \mathbf{b}$ in a direction that is perpendicular to the plane.

The line joining the fixed nodes is the border between positive and negative half-planes. The metric value is zero on that line, and 1 or -1 at the circle with the fixed points diametrically opposite (the diameter of the circle subtends a right angle).

In our three-dimensional case, we have three fixed nodes (such as A, B and C in Figure 1) for each element attached to the moving node P. The plot of j , as a function of the three node coordinates, is a 4D surface for each attached element. The planes through each triplet of fixed nodes, are the borders between positive and negative half-spaces. For each attached trihedron, any pair of fixed points (say A and B) defines a sphere (in which A and B are diametrically opposite). If the node were on the surface of that sphere, the edges (PA and PB) will form a right angle. In order that the three edge angles are right (j equals 1 or -1), the node must be at the intersection between the three spheres so defined (by AB, BC and CA). This intersection exists as long as the fixed nodes are forming an acute triangle (ABC).

Thus, when the metric is negative, we use J (the triple product of the edge vectors) without dividing it by the edge lengths. It does not require a new calculation when it is negative, it is not divided by the edge lengths.

This combination of metric values is one of the key approaches to successfully untangle meshes having nodes with negative Jacobian.

Figure 3(a) displays a node P from a two-dimensional planar mesh and the quadrilatera sharing that node. The adjacent nodes are labelled A_i , and the diagonally opposite ones are labelled D_i . Shown in (b) is the enveloping polygon of the adjacent nodes. *The quality of P is positive only if the node is inside the kernel of that polygon.* If the point is moved out of the kernel, at least one of the attached elements will be inverted.

In the three-dimensional case we have an enveloping polyhedron, trihedral solid angles and a convex kernel polyhedron yielding positive metric to all the trihedra attached to the node.

In order to avoid futile attempts to improve a node whose quality cannot be bettered any more, we need a value for the maximum quality attainable by each node. The positions of the neighbouring nodes severely restrict that value, but these positions will change in successive steps.

Figure 3. Envelope and Kernel of the nodes adjacent to a node P.

Figure 4. Envelope and Kernel of the element set attached to a node P.

Figure 5. Fixed boundary node.

The valence of the node (the number of attached edges), in turn, limits the quality and this limit will not change.

In 2D the minimum angle at a node with n elements attached cannot be over $360^\circ/n$. In 3D the general function relating the upper bound on j with the number of edges is the same problem as the optimal placing of points in a spherical surface. It is an unsolved combinatorial geometry problem [11, 12], so we currently do not provide the program with such a value.

If we analyze Figure 3(b) and Figure 4 we can easily see that, by increasing the quality of a node, we may negatively affect that of its neighbours. Even in the kernel of the adjacent nodes, where the node P has positive-metric, some of the attached nodes can take negative metric values.

The cluster-enveloping polygon, formed with the attached elements, has a smaller kernel (with a higher probability of being void) than the adjacent nodes envelope. In the cluster kernel, the node has a positive metric and does not force a negative metric on its neighbour nodes. It is evident that the centroid of the cluster kernel is a better position for the node than the commonly used

(Laplacian) centroid of the envelope. As the kernel is difficult to obtain in 2D, obviously our 3D case is even harder. Any algorithm doing that will be welcomed.

2.3. Boundary nodes

The boundary of the hexahedral mesh is a closed quadrilateral mesh with fixed nodes. We will show how the quality of the hexahedral mesh is affected by the quality of the prescribed boundary.

Our hexahedral mesh generator makes one element for each face of the outer mesh. As was explained in previous works [5, 6], a layer of elements adjacent to the boundary composed of one hexahedron for each quad, makes it possible to correct many potential problems with the outermost elements.

Figure 5 above displays an external node O with one of the n trihedra sharing the segment OP . In addition, we can see S_O^2 (unit sphere at O), the greyed sector left by S_O^2 at the i th external quad, and the corresponding unit vectors. Translating the origin of coordinates to O , we have (as P moves) the metric of the i th trihedron:

$$j_i = (\mathbf{a}_i \mathbf{a}_{i+1} \mathbf{p}) = (\mathbf{a}_i \times \mathbf{a}_{i+1}) \cdot \mathbf{p} \Rightarrow \nabla j_i = \mathbf{a}_i \times \mathbf{a}_{i+1}, \quad \text{with the indices cycling modulus } n \quad (3)$$

The maximum j_i is for $\mathbf{p}$ perpendicular to the i th face (actually, to the triangle $A_i O A_{i+1}$).

The direction $\mathbf{p}$ is *a priori* unknown, so the worst j_i is also unknown but we can say that it is worse (lesser) than the worst $\mathbf{a}_i \times \mathbf{a}_{i+1}$. Therefore, the quality of the mesh is conditioned from the beginning by the worst (two dimensional) j_i of the quads, i.e. the quality of the exterior mesh.

This simple bound is a poor approximation, as the scalar product will lower the actual quality in acute polyhedral angles.

The calculation of the limit on the orthogonality reachable by any border node has the same difficulty level as the calculation of the optimal position of any node and so we do not perform it; however, it is a source of time consumption when the program makes futile attempts to improve beyond imposed restrictions.

register for free at <https://www.scipedia.com> to download the version without the watermark

3. PROGRAMMING

Our goal is to move each node to a better position. To compare positions, we use the quality of the node as well as the worst quality from the set made up of the node and its neighbours.

So, in our algorithm, *a new position for the node P is considered to be better if the worst quality of the set $\{P, \{A_i\}\}$ improves or if it stays the same and the quality of the node improves.*

Every previous attempt we made by using only analytical ways invariably ended up with some locking positions, often with negative metric.

In order to select the nodes to be moved, a list in reverse quality order is made. The first nodes on the list are selected and tested one at a time. This sub-list is repeatedly traversed. The quantity of tested nodes is a function of the overall quality of the mesh, starting with a few nodes and expanding to the entire list as the quality rises, or when there is no significant improvement.

To change a node position, the program has three different approaches:

(1) *Gradient driven:* As was explained before, a node movement in a direction improving the worst trihedron quality (∇j) may lower the quality of the neighbour nodes. Thus, the program makes a minimum movement in that direction; if it is a better position (in the sense already defined), the maximum successful step in that direction is found.

The obvious choice for the reference step is

$$\|\Delta P\| = \frac{1-j}{\|\nabla j\|} \Rightarrow \Delta P = \frac{1-j}{\|\nabla j\|^2} \nabla j \quad (4)$$

This step carries j to 1 (orthogonal trihedron), but it has proven less efficient than the mean length of the edges attached to the node. Labelling a_i the i th edge length $\|A_i P\|$, and considering that there are n such attached edges, we choose the reference movement length

$$\|\Delta P\| = \langle a_i \rangle = \frac{\sum \|A_i P\|}{n} \quad (5)$$

The first (and minimum) attempt is $\frac{1}{128}$ of this. If it is successful, we test the whole reference step. If it does not succeed, we halve it recursively until a movement improving the node quality is found.

If the minimum movement does not succeed, the control passes to the next algorithm.

(2) *Simulated annealing*: The node is randomly moved and tested. The movement steps randomly take different directions and their magnitudes are random fractions of the mean edge length (previously calculated)

$$\|\Delta P\| = f \langle a_i \rangle, \quad \text{where } 0 < f \leq 1 \quad (6)$$

The number of attempts is a linear function of quality, between 0 for quality 1 and 50 attempts when quality falls to 0 or negative.

(3) *Forced movement*: If all the previous tricks have failed and

- (a) the quality of the node is 0 or negative,
- (b) this is the sixth time with this node and is still unchanged,
- (c) the node has at least one positive-metric neighbour node.

Then, the node and its neighbours are forced to move randomly as defined in the previous algorithm.

This movement is meant to prevent severe locking of a node. The causes may vary, but it actually happens and this solution works out well.

The third condition lies in the fact that almost every example we tested has a near-smooth layer of many negative-metric nodes (mostly at the domain frontier). It is useless to work inside this layer so we chose to move only those nodes at the interface with the ones having a good position.

Finally, the program halts if the required quality is reached, or some prescribed time has passed or the list of nodes is complete and the quality does not improve.

Even though all the factors and functions chosen were experimentally tested, we do not expect them to be the best (fastest) values for every situation. We can only say that these values gave positive metric meshes in all our examples and benchmarks. Many of them may seem superfluous, inefficient or extremely conservative, but they are necessary in order to guarantee the result. Regardless of whether it takes a minute or an hour, the speed must not interfere with the robustness.

4. EXAMPLES

The examples were tested in an ALPHA station 500, 333 MHz with 320 MB of RAM and Digital UNIX V4.0B operating system.

Figure 6. Mesh with an acute concavity.

Figure 7. Run plot of quality for the curved beam.

We have tested mostly benchmark, few-element meshes without any engineering sense; however, we have selected three examples of concave meshes to be shown here.

In order to test the robustness of the process, all the runs were made with the same set of parameters.

4.1. Curved beam

The first example is a test case of an acutely curved beam (Figure 6), forcing bad results from Laplacian-only smoothing. The resulting hexahedral mesh has 1586 nodes and 1310 elements.

Figure 8. Mesh for a gear tooth.

Figure 9. Run plot of quality for the tooth.

The running test started with 150 negative-quality nodes. They reached the 0-quality status in a minute and the overall quality rose to an acceptable level >0.1 (about 6 or 174°) in less than 2 min (Figure 7).

In the plots, mean, minimum and standard deviations are over the set of node qualities, being 1 for a perfectly orthogonal trihedron, 0 when squashed on a plane and negative when inverted.

4.2. Gear tooth

The second and more complex example shown in Figure 8 is a test problem of a gear tooth from a contact problem. The planar mesh was made by using a planar paving [13] mesh-generator and then extended and refined in the third dimension with the help of a CAD program. The all-hexahedral mesh has 9286 nodes and 8210 elements.

Figure 10. CAD Mesh for a spherical bearing.

Figure 11. Run plot of the spherical bearing, starting with the Laplacian-smoothed mesh.

The initial situation with 404 negative nodes was corrected in about 10 min and the mesh quality reached an acceptable level in 15 min (Figure 9).

4.3. Spherical bearing

The external mesh for the spherical bearing shown in Figure 10 was entirely made with a standard PC CAD program. The corresponding all-hexahedral mesh has 68689 nodes and 60112 elements.

Starting with the Laplacian smoothed mesh, the initially negative 56 nodes were corrected in less than a minute, and it took a total of 11 min to improve the overall quality (Figure 11).

5. CONCLUSIONS

The problem of finding the best shape for the elements/nodes of an all-hexahedral mesh has proven intractable by some of the standard means used with tetrahedrons.

Although there is still a lack of consensus about the best-quality measure for hexahedral elements, we made some progress towards the improvement of angular quality.

Surely this metric alone is not the solution. It must be combined with suitable values for the aspect ratio and the planarity of the faces in order to boost the overall quality of the mesh. We actually use a product made up of the metric already presented and a node-based measure of aspect ratio related to the logarithm of the quotient between minimum and maximum lengths from the set of attached edges.

The method has proven to be robust and every test has given a positive result, so it can be easily extended to any quality measuring value. The very philosophy of the object-oriented programming allows us to replace the metric used by any other.

We are now in a position to make good-quality meshes for the type of problems that can be successfully addressed by our all-hex generator.

REFERENCES

1. Canann SA, Tristano JR, Staten ML. An approach to combined Laplacian and optimization-based smoothing for triangular, quadrilateral and quad-dominant meshes. *7th International Meshing Roundtable*, Michigan, 1998.
2. Owen SJ. *A Survey of Unstructured Mesh Generation Technology*, Chapter 5: Mesh Post-Processing. <http://www.andrew.cmu.edu/user/sowen/survey/postsurv.html>
3. Reitag LA, Knupp PM. Tetrahedral element shape optimization via the Jacobian determinant and condition number. *8th International Meshing Roundtable*, California, 1999.
4. Knupp P. Achieving finite element mesh quality via optimization of the Jacobian matrix norm and associated quantities, Parts I and II. *Technical Report SAND 99-0709J*, Sandia National Laboratories, 1999.
5. Calvo NA, Idelsohn SR. Generador automático de mallas de hexaedros: presentación del método y avances en la implementación. *Mecánica Computacional Vol XVI*, Asociación Argentina de Mecánica Computacional, 1996.
6. Calvo NA, Idelsohn SR. All-hexahedral element meshing: Generation of the dual mesh by recurrent subdivision. *Complementary Methods in Applied Mechanical Engineering* 2000; **182**:371–378.
7. Tautges TJ, Blacker TD, Mitchell SA. The whisker weaving algorithm: a connectivity-based method for constructing all-hexahedral finite element meshes. *International Journal for Numerical Methods in Engineering* 1996; **39**: 3327–3349.
8. Knupp P. Applications of mesh smoothing: copy morph, and sweep on unstructured quadrilateral meshes. *International Journal for Numerical Methods in Engineering* 1999; **45**:37–45.
9. Freitag L, Jones M, Plassmann P. An Efficient Parallel Algorithm for Mesh Smoothing. *Proceedings of the 4th International Meshing Roundtable* 1995; 47–58.
10. Preparata P, Shamos M. *Computational Geometry*. Springer: New York, 1985.
11. McCaughan G. Circle Packings. <http://www.pmms.cam.ac.uk/~gjm11/cpacking/info.html>.
12. Bourke P. Distributing Points on a Sphere. <http://www.mhri.edu.au/~pdb/geometry/spherepoints/>.
13. Blacker TD, Stephenson MB. Paving: a new approach to automated quadrilateral mesh generation. *International Journal for Numerical Methods in Engineering* 1991; **32**:811–847.