Exascale Quantification of Uncertainties for
Technology and Science Simulation

D7.1 - DELIVERY OF GEOMETRY AND COMPUTATIONAL MODEL

Document information table

Contract number:	800898
Project acronym:	ExaQUte
Project Coordinator:	CIMNE
Document Responsible Partner:	str.ucture GmbH
Deliverable Type:	Other
Dissemination Level:	Confidential
Related WP & Task:	WP7 7.1
Status:	V00

Authoring

Prepared by: str.ucture GmbH				
Authors	Partner	Modified Page/Sections	Version	Comments
Alexander Michalski	STR	Complete document	00	
David Andersson	STR	Complete document	00	

Change Log

Versions	Modified Page/Sections	Comments
00		Creation of document

Approval

Approved by:				
	Name	Partner	Date	OK
Task leader	Alexander Michalski	STR	31-7-2019	✓
WP leader	Roland Wüchmer	TUM	31-7-2019	✓
Coordinator	Riccardo Rossi	CLMNE	31-7-2019	✓

Register for free at <https://www.scipedia.com> to download the version without the watermark

Summary

This document describes the industrial application, on which the developments of the project are implemented, and the CFD set-up. The developments are implemented over six analysis cases with increasing complexity starting from a 2D geometry with mean wind inflow to a 3D geometry with turbulent inflow and real-time shape optimization. The application represents the CAARC tall building model, which has served as a benchmark model for many studies since the 1970's when it was first developed. Base moments (bending and torsional moments) of the building are extracted for validation by comparison of the results with the benchmark study.

Register for free at <https://www.scipedia.com> to download the version without the watermark

Table of contents

1	Introduction	7
1.1	Benchmark study	7
1.2	CAARC standard tall building	8
1.3	Target values	9
2	CFD set-up	10
2.1	Turbulence modelling and inflow conditions	10
2.2	Wind parameters	10
2.3	Computational domain and orientation	11
2.4	Boundary conditions	13
3	Deliverable	14
A	Analysis cases	15
A.1	Case 1	15
A.2	Case 2	15
A.3	Case 3	15
A.4	Case 4	15
A.5	Case 5	15
A.6	Case 6	16
B	Benchmark results	17

Register for free at <https://www.scipedia.com> to download the version without the watermark

List of Figures

1	Dimensions of the CAARC standard tall building model [m].	8
2	Dimensions of computational domain.	11
3	Local orientation of the building.	12
4	Boundary conditions.	13
5	Mean base moments around local $\tilde{X}$ -axis for the seven test groups [3, 4]. .	17
6	Mean base moments around local $\tilde{Y}$ -axis for the seven test groups [3, 4]. .	18
7	Mean base moments around local $\tilde{Z}$ -axis for the seven test groups [3, 4]. .	18

List of Tables

1	Wind parameters to be used in the study.	10
---	--	----

Register for free at <https://www.scipedia.com> to download the version without the watermark

Nomenclature / Acronym list

Acronym	Meaning
CAD	Computer Aided Design
CFD	Computational Fluid Dynamics
v_{ref}	Reference wind speed
z_{ref}	Reference height
α	Power law exponent

Register for free at <https://www.scipedia.com> to download the version without the watermark

1 Introduction

There is a great potential applying advanced computational wind engineering methods in the field of high-rise structures, as there is an increasing need worldwide to build more and slender, and hence wind prone, high-rise structures in densely urbanized parts of the world. A high-rise building is therefore chosen as the industrial application, on which the developments of the project are implemented.

1.1 Benchmark study

To be able to validate the wind forces on the structure, the numerically obtained results has to be compared with either wind tunnel tests or on-site measurements. In this study the comparative *International high-frequency base balance benchmark study* [3] will act in this purpose.

The initiative for the benchmark study was taken during a meeting held at the 12th International Conference on Wind Engineering in July 2007 [3]. The study was conducted between the years 2007 and 2011 where eight international wind-tunnel laboratories carried out independent tests and subsequently presented their results for comparison [3].

The study was carried out on two prescribed tall building models.

- A "basic" building model intended to serve as a benchmark for newer test groups.
- An "advanced" building model intended to serve as a benchmark for more experienced test laboratories.

Register for free at <https://www.scipedia.com> to download the version without the watermark

The former of the two is a metric version of the Commonwealth Advisory Aeronautical Council (CAARC) standard tall building model [4] which is hereinafter the model used in this study.

1.2 CAARC standard tall building

The CAARC standard tall building model was developed in 1970 [6] for analysis of wind loading on tall buildings. It has since then been one of the more popular high-rise building models for wind tunnel studies, as it originally was developed for, but has in recent times also been used extensively as application for numerical CFD analysis [1].

Register for free at <https://www.scipedia.com> to download the version without the watermark

Figure 1: Dimensions of the CAARC standard tall building model [m].

1.3 Target values

It is known that only base moments are not sufficient for designing a structure. However, due to the complexity of the developments that are to be implemented the target values are chosen as simple as possible but at the same time sufficient enough to be able to validate the study.

The benchmark study presents resulting mean base moments (bending and torsional moments) of the building, shown in Appendix B. Mean base moments are thus used as target values also in this study.

Register for free at <https://www.scipedia.com> to download the version without the watermark

2 CFD set-up

2.1 Turbulence modelling and inflow conditions

The Large-Eddy Simulation (LES) is used throughout the study to model the turbulence.

To model the natural wind conditions at the inlet the velocity boundary condition is separated into one mean wind part and one fluctuating part, described in the equation below.

$$v_i(z, t) = \bar{v}_i(z) + v'_i(z, t) \quad (1)$$

The mean wind part is generated using the power law (cf. chapter 2.2) and the fluctuating part is generated by an algorithm described by Jakob Mann [5].

2.2 Wind parameters

The mean wind profile is generally described by the power law.

$$\bar{v}(z) = v_{ref} \left(\frac{z}{z_{ref}} \right)^\alpha \quad (2)$$

The parameters that describes the wind profile depend on local design wind speeds and the terrain. The parameters to be used in this study are corresponding to the ones used in the benchmark study and are presented in the table below.

Register for free at <https://www.scipedia.com> to download the version without the watermark

Table 1: Wind parameters to be used in the study.

Parameter	Value
v_{ref}	20 [m/s]
z_{ref}	10 [m]
α	0.25

2.3 Computational domain and orientation

It is recommended to place the inlet surface, the lateral surfaces and the top surface $5H$ away from the building and the outlet surface $15H$ away from the building ($6H \times 10H \times 20H$), where H is the total height of the building, according to the guidelines of CFD simulations in wind engineering [2].

These recommendations generates a quite big and expensive computational domain, the effects of a smaller computational domain was therefore investigated by Daniels et al. It is stated that the results obtained with a smaller domain ($4H \times 8H \times 10H$) were consistent with the results obtained with the bigger domain [1], the smaller domain was thus used throughout their study.

With the aim of doing the analysis more economic the size of the computational domain of the present study will follow those used by Daniels et al.

Figure 2: Dimensions of computational domain.

The orientation of the building is chosen to align with that from the benchmark study (cf. figure 3).

Figure 3: Local orientation of the building.

2.4 Boundary conditions

The boundary conditions are chosen in line with the benchmark study. The lateral surfaces and the top surface are set to symmetry-planes and a no-slip condition is assigned on the bottom of the domain and on the walls of the CAARC building [1, 3].

Figure 4: Boundary conditions.

3 Deliverable

A CAD model of the CAARC building can be delivered to the PO if required.

Appendix A Analysis cases

The complexity of the analysis is gradually increased over six analysis cases where the basic set-up for each individual case is presented below.

A.1 Case 1

Geometry:	2D 30x180 [m]
Computational domain:	1080x3600 [m]
Inflow conditions:	Mean wind profile
Morphing:	None
Target value(s):	Base moment $M_{\tilde{X}}$

A.2 Case 2

Geometry:	2D 30x180 [m]
Computational domain:	1080x3600 [m]
Inflow conditions:	Turbulent wind profile (Mann model)
Morphing:	None
Target value(s):	Base moment $M_{\tilde{X}}$

A.3 Case 3

Geometry:	3D 30x45x180 [m]
Computational domain:	1080x1800x3600 [m]
Inflow conditions:	Mean wind profile
Morphing:	None
Target value(s):	Base moments M_i ($i = \tilde{X}, \tilde{Y}, \tilde{Z}$)

A.4 Case 4

Geometry:	3D 30x45x180 [m]
Computational domain:	1080x1800x3600 [m]
Inflow conditions:	Mean wind profile
Morphing:	Real-time shape optimization
Target value(s):	Base moments M_i ($i = \tilde{X}, \tilde{Y}, \tilde{Z}$)

A.5 Case 5

Geometry:	3D 30x45x180 [m]
Computational domain:	1080x1800x3600 [m]
Inflow conditions:	Turbulent wind profile (Mann model)
Morphing:	None
Target value(s):	Base moments M_i ($i = \tilde{X}, \tilde{Y}, \tilde{Z}$)

A.6 Case 6

Geometry:	3D 30x45x180 [m]
Computational domain:	1080x1800x3600 [m]
Inflow conditions:	Turbulent wind profile (Mann model)
Morphing:	Real-time shape optimization
Target value(s):	Base moments M_i ($i = \tilde{X}, \tilde{Y}, \tilde{Z}$)

Appendix B Benchmark results

Figure 5: Mean base moments around local $\tilde{X}$ -axis for the seven test groups [3, 4].

Figure 6: Mean base moments around local $\tilde{Y}$ -axis for the seven test groups [3, 4].

Figure 7: Mean base moments around local $\tilde{Z}$ -axis for the seven test groups [3, 4].

References

- [1] S. Daniels et al. Peak loading and surface pressure fluctuations of a tall building model. *Journal of wind engineering and industrial aerodynamics*, 120, 2013.
- [2] J. Franke et al. Recommendations on the use of CFD in wind engineering. *Cost action C*, 14, 2004.
- [3] J. Holmes et al. International high-frequency base balance benchmark study. *Wind and Structures*, 18:457–471, 2014.
- [4] IAWE et al. Benchmark Buildings for an International HFBB Comparison. *International Association for Wind Engineering*, 2012.
- [5] J. Mann. Wind field simulation. *Probabilistic Engineering Mechanics*, 13:269–282, 1998.
- [6] R. Wardlaw et al. A standard tall building model for the comparison of simulated natural winds in wind tunnel. *CAARC, CC 662m Tech 25*, 1970.