Goal-Oriented *hp*-Adaptive Finite Element Methods: A Painless Multi-level Automatic Coarsening Strategy

Felipe V. Caro*, Vincent Darrigrand†, Elisabete Alberdi Celaya††, and David Pardo†††

* Basque Center for Applied Mathematics (BCAM)
University of the Basque Country (UPV-EHU)
Alameda Mazarredo 14, 48009 Bilbao, Spain
e-mail: msc.felipe.caro@gmail.com

† CNRS-IRIT,
Toulouse, France
email: vincent.darrigrand@gmail.com

†† University of the Basque Country (UPV-EHU),
Bilbao, Spain
email: elisabete.alberdi@ehu.eus

††† University of the Basque Country (UPV-EHU),
Basque Center for Applied Mathematics (BCAM),
Ikerbasque,
Bilbao, Spain
email: dzubiaur@gmail.com

ABSTRACT

In many engineering applications, the global energy of the problem may be a quantity of limited relevance. This motivated the design of goal-oriented adaptive finite element methods (see e.g. [1,4-6]). They intend to approximate a particular Quantity of Interest (QoI) using an error estimator based on the solution of the adjoint problem to guide the refinements. In this framework, Darrigrand et al. [3] presented an alternative dual operator for the representations of the error in the QoI.

In the context of *hp*-adaptivity, Darrigrand et al. [2] proposed an algorithm for symmetric and positive definite (SPD) problems based on performing global refinements followed by optimal unrefinements. This algorithm marks the basis functions with the lowest contributions to the energy of the solution and remove them. The resulting automatic *hp*-adaptive strategy employs a multi-level hierarchical data-structure proposed by Zander et al. [7].

In this presentation, we extended Darrigrand et al. [2] algorithm to non-SPD problems in the framework of goal-oriented adaptivity. To do so, we evaluate the contribution to the energy in the alternative dual operator proposed by Darrigrand et al. [3], thus, considering both the direct and the adjoint problem.

As a result, we obtain an *hp*-adaptive algorithm for SPD and non-SPD problems in the context of goal-oriented adaptivity. We test and analyze our algorithm on two-dimensional (2D) Laplace, Helmholtz, and convection-dominated problems. We also describe the main features and limitations of the proposed method. In particular, our algorithm is robust and simple to implement; therefore, it can be used for industrial applications.

REFERENCES

- [1] Becker, R., & Rannacher, R. (1996). *Weighted a posteriori error control in FE methods*. IWR.
- [2] Darrigrand, V., Rodríguez-Rozas, Á., Muga, I., Pardo, D., Romkes, A., & Prudhomme, S. (2018). Goal-oriented adaptivity using unconventional error representations for the multidimensional Helmholtz equation. *International Journal for Numerical Methods in Engineering*, 113(1), 22-42.
- [3] Darrigrand, V., Pardo, D., Chaumont-Frelet, T., Gómez-Revuelto, I., & Garcia-Castillo, L. E. (2020). A painless automatic *hp*-adaptive strategy for elliptic problems. *Finite Elements in Analysis and Design*, 178, 103424.

- [4] Oden, J. T., & Prudhomme, S. (2001). Goal-oriented error estimation and adaptivity for the finite element method. *Computers & mathematics with applications*, 41(5-6), 735-756.
- [5] Prudhomme, S., & Oden, J. T. (1999). On goal-oriented error estimation for elliptic problems: application to the control of pointwise errors. *Computer Methods in Applied Mechanics and Engineering*, 176(1-4), 313-331.
- [6] Rannacher, R., & Suttmeier, F. T. (1998). A posteriori error control in finite element methods via duality techniques: Application to perfect plasticity. *Computational mechanics*, 21(2), 123-133.
- [7] Zander, N. D. (2017). *Multi-level hp-FEM: dynamically changing high-order mesh refinement with arbitrary hanging nodes* (Doctoral dissertation, Technische Universität München).

Register for free at <https://www.scipedia.com> to download the version without the watermark